Residential downlights.

01604 495 151 collingwoodlighting.com

𝒴 @collingwoodLED

f /collingwoodlighting

O collingwoodled

GUARANTEE / WARRANTY

3 year extended warranty

FEATURES & BENEFITS

Loop-in loop-out connector for ease of installation

30, 60, 90 min fire rating providing additional safety

Acoustic and moisture tested

6-Watt LED or 50-Watt halogen lamp compatible for additional versatility

IP65

Lamp not included



GU10 Downlight

Fire-rated fixed IP65 downlight

FEATURES

IP rating	IP65
Tiltable	No
Input	Mains AC

INSTALLATION INFORMATION

Install connector type	Push-fit terminal connector
Insulation coverable	No
Cut out size	Ø 79mm
Construction material	Mild steel
Maximum ceiling thickness	40mm
Weight	0.259g
Building regulations	Part B, C, E, P
Electric class (1, 2, 3)	1

PRODUCT CODE

Product code	Finish	Description
CWFRC004	Matt white	GU10 Fire rated downlight, Fixed, IP65, White
CWFRC005	Brushed steel	GU10 Fire rated downlight, Fixed, IP65, Brushed steel
CWFRC006	Polished chrome	GU10 Fire rated downlight, Fixed, IP65, Polished chrome

WIRING INFORMATION

Cable / flying lead	N/A
Cable required for connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²)
Type of wiring required	Parallel

