

**ARCA 403015**



Sample photo

**Order symbol:** ARCA 403015  
**Product nbr:** 8120006  
**Description:** Cabinet, PC  
**Remarks:** Grey cover, 2-point locking, hinges on the long side

**EAN:** 6418074079176  
**EI. number:**  
 Finland: 3423051  
 Denmark: 8212091045  
 Sweden: 2500112  
 Norway:

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key.  
 S versions with swinghandle 3-point locking system. F versions with flange opening. Door guide included.

Dimensions:		Length	Width	Height	Rating:
<b>mm:</b>		400	300	150	Ingress Protection (EN 60529): IP 66
<b>inch:</b>		15.7	11.8	5.9	Impact Resistance (EN 62262): IK 10 +35°C /IK 08 -25°C
<b>Materials:</b>					Electrical insulation: Totally insulated
<b>Material:</b>		Polycarbonate			Halogen free (DIN/VDE 0472, Part 815): Yes
<b>Base colour:</b>		RAL 7035			UV resistance: UL 508
<b>Cover colour:</b>		RAL 7035			Glow Wire Test (IEC 695-2-1) °C: 960
<b>Gasket material:</b>		PUR			<b>Certificates:</b>
<b>Temperatures:</b>					Fimko
<b>Short term:</b>		-40 ... 120 °C			
<b>Continuous:</b>		-40 ... 80 °C			
<b>Short term:</b>		-40 ... 250 °F			
<b>Continuous:</b>		-40 ... 175 °F			
<b>Accessories:</b>					
MPS ARCA 4030		Mounting plate			
MPP ARCA 4030		Mounting plate perforated			
MPX ARCA 4030		Mounting plate			
DRS ARCA 403015		DIN rail frame set			
DRS ARCA 403021		DIN rail frame set			
IDS ARCA 4030		Inner door set			
PMK ARCA 30		Pole mounting kit			

