

JC71744 Skypack QR LED Batten 5ft Twin IP20 4000K 60W 7200Lm



Features & Benefits

- Intelligent press release buttons for simple installation
- Ultra efficient, up to 120 lumens per circuit Watt
- Suspended LED tray for easy installation
- Press fit terminals, loop in loop out
- Rear and end conduit entry points
- Microwave dimmable options

General Information

Product Group	LED - Surface
Product Range	Skypack™
Trade Name	Skypack™ QR
Light Source	LED
Light Source Features	Neutral White
Lighting Product Type	Linear Lighting
Product Shape	Rectangular
Mounting	Surface Mounted
Product Weight	2.75kg
Color Finish	White
Overall Dimensions	1523 x 70 x 76.5

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Driver Manufacturer	Ledtu	
Warranty	2 years standard warranty extends to 5 years when registered within the first year of purchase (See Website for terms and conditions)	
Origin Of Manufacture	Made In China	
Environment	Indoor	
IP Rating	IP20	
Method Of Fix	Surface with Conduit Entry	
Recommended Product Location	Domestic, Commercial and Industrial Applications	

Electrical

Voltage Rating	220-240
Secondary Running Current	1400mA
Primary Running Current	350mA
Operating Frequency (Hz)	50/60Hz
CC or CV	Constant Current
Luminaire Circuit Wattage	60
Class	Class I
Output Voltage (V)	27-40VDC
EMC Compliant (EN55015)	Yes
Power Factor Correction	0.9
Input Electrical Connections	Live, Earth & Neutral
Dimmable	No

Thermals

Room Ambient Temperature Not To 30°C **Exceed**

Performance Data

Energy Rating	A+
Actual Lumen Output	7200
Lumens Per Circuit Watt	120
LED Life (Hours) (L70)	54000
	Hours life stated is an indication of expected L70 chip and light output calculations wher operating in optimum conditions. Product warranty period supports the full product during the term given. The L70 hours expectancy is not correlated with the full product warranty term, nor is it a representation of lumen depreciation during the warranty period.
Color Rendering Index	80-89
CRI: Ra	80
Correlated Color Temperature	4000K
Light Distribution Detail	120-degree
LOR (Light Output Ratio) %	100

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk

Photometry Available	Photometry	/ Available
----------------------	------------	-------------

Yes

Construction

Primary Material	Steel
Diffuser	Polycarbonate
Outer Diffuser	Polycarbonate

Packaging


Quantity Per Outer Carton	8
Bar Code EAN Number	5052544080470
Packaged Weight	2.63kg

Standards & Approvals

Listings	CE
Listings	RoHS
Manufactured In Accordance To	BS EN 60598:2015, 2-1
CE Marked	Yes
Batch Coded	Yes
WEEE Symbol	Yes
Certificate Of Conformity	Yes: available on request.
Accredited Members	LIA, ISO9001:2015, ISO14001:2015

JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS Company Registration Number: 03044848 | VAT Number: 918544112



JCC Lighting

Innovation Centre, Beeding Close, Southern Cross Trading Estate, Bognor Regis, West Sussex, PO22 9TS Company Registration Number: 03044848 | VAT Number: 918544112

T: 01243 838999 | F: 01243 838998 | sales@jcc.co.uk | www.jcc.co.uk