



Retrofit Surge Protection Units

- Suitable for use on TN-C-S (PME) / TN-S / & TT networks
- Provides protection against the effects of transient over voltages
- Ideal for installation where it is not possible to accommodate a suitable surge arrester directly within the existing consumer unit.



SRG1VCU-RM

TECHNICAL DATA		REGISTRY	
Surge protective class	Type 2-3	Net weight	1.87KG
Manufacturing material	Steel	Gross Weight	1.93KG
Protection degree	IP2X	EAN Code	5026992043110
Description	cw Main Sw, MCB & SRGT2CU	Min order quantity	1.00
Frequency	50-60Hz	Dimensions	250x135x87mm (HWD)
Phase	1		
Rated operating voltage	230V		
Earthing Systems	TN-C-S-(PME)		
Earthing Systems	TT		
Earthing Systems	TN-S		
Nm dischar. current(In)(8/20uS20kA (L/N,L/PE)			
Nm dischar. current(In)(8/20uS40kA (N/PE)			
Voltage protection level (Up)	<1,5kV (L/N)		
Voltage protection level (Up)	<1,5kV (L/PE)		
Voltage protection level (Up)	<1,5kV (N/PE)		
For cables ø	35mm ²		
		REFERENCE STANDARDS	STANDARDS
		IEC 61643-11:2011	
		EN 61439-1:2011	
		EN 61439-2:2011	
		EN 61643-11:2012	